

**PRODUCT DESCRIPTION :**

Unique Water Protection is a acrylic Solvent base single pack with highly efficient saving elastomeric coating designed to water proofing. It is base on elastomeric polymer blended white special ceramic micro spheres that acts as a thermally efficient blanket. Non toxic and environmental friendly.

**RECOMMENDED USE**

Use on fireproof coating for structural steel supports for equipment , pipe racks and tower skirts should require mechanical reinforcement , metal lath , hardware cloth , etc .

**PHYSICAL DATA**

Colour	White
Solid content (%)	76 ± 2
Specific gravity	1.25 - 1.30
Gloss	Matt
Surface	Steel
Film thickness recommended	200 microns dry film
Theoretical coverage	52 sq. m / 22 Kg.

**SYSTEM RECOMMENDED**

<b>Enamel system</b> - Neocoat Primer	<b>Epoxy system</b> - Superguard HB-SS
- Neocoat Intumescent Paint -S	- Neocoat Intumescent Paint -S
- Unique Water Protection	- Unique Water Protection
- Neogloss Enamel	- Superguard PU 777

**APPLICATION DATA**

Application method	Brush , Roller and Airless spray
Cleaner/Thinner	Victor Thinner AAA

**SURFACE PREPARATION**

Surface is clean and dry. All loose, and flaking paint must be removed.

**STORAGE AND HANDLING**

Storage	The product must be store in well ventilated place protected from high temperature. Container must be kept tightly closed .
Handing	Handle with care. Stir well be for use.
Packing	5 US gal.

**HEALTH AND SAFETY**

Avoid contact with skin and eyes wear. Wear suitable protective clothing such as overalls during painting. Avoid skin contact. Spillage on skin should immediately be remove with soap and water. Eyes should be flushed flushed with water and medical attention sought immediately.