

## Technical Data Sheet

### FOUR PLUS EMUSION EXTERIOR

#### PRODUCT DESCRIPTION :

A standard quality acrylic emulsion paint is base on a 100% acrylic emulsion and the light fasted pigments to give excellent durability and excellent resistance to fungus attack alkali on plaster and weathering

#### RECOMMENDED USE :

suitable for the decoration and protection of all Exterior building surface . Typical Use ;It is ideal for application to both exterior , concretes,new and old masonry surfaces,plasters,bricks,asbestos shingled and siding.

#### TECHNICAL INFORMATION :

|                      |                             |
|----------------------|-----------------------------|
| Type                 | 100% Acrylic Emulsion Paint |
| Color                | According to Color card     |
| Film Appearance      | Matt                        |
| Solid Content (%)    | 35±2                        |
| Flash Point          | N/A                         |
| Dry Film Thickness   | 35      microns             |
| Theoretical Coverage | 150      Sqm. / Pail / Coat |

Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated.

|                          |                  |
|--------------------------|------------------|
| Touch Dry    (25-30 °C)  | 30      minutes. |
| Recoat Dry    (25-30 °C) | 2      hours.    |
| Hard Dry      (25-30 °C) | 72      hours.   |

#### PRODUCT STANDARD :

TIS 1123-2539 (Weather Resistance Emulsion Paint )

#### APPLICATION :

|                   |                        |
|-------------------|------------------------|
| Tools             | Roller / Brush / Spray |
| Mixing / Cleaning | Clean Water            |
| Dilution (%)      | 20-25    %             |

## Technical Data Sheet

### FOUR PLUS EMUSION EXTERIOR

#### APPLICATION SYSTEM :

##### Surface preparation

##### Old Surface

Powdery and chalky surface must be scrubbed and cleaned with water Fungus and mildew growth must be cleaned off . Left to dry for 2-3 days

##### New Surface

Substrate must be completely cured and dried ( ~ 1 month ) free from oil ,grease ,mildew,from release agents and foreign matters.or measure moisture which should be less than 15% on surface with protimeter mini If any crack, it should be repaired on surface before applying.

##### Painting System

##### Primer for Old Surface

1 Coat of NEOCOAT MASONRY SEALER

##### Primer For New Surface

1 Coat of FOUR PLUS ALKALI RESISTING PRIMER

##### Topcoat

2 Coats of FOUR PLUS EXTERIOR

#### HANDLING AND STORAGE :

##### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

##### Shelf Life

2 years

##### Packing

18.925 Ltr.

#### HEALTH AND SAFETY :

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.