

Technical Data Sheet

FOUR PLUS PRO EMUSION INTERIOR

PRODUCT DESCRIPTION :

A high quality acrylic emulsion paint is base on a 100% acrylic emulsion and the light fasted pigments to give excellent durability and excellent resistance to fungus attack alkali on plaster and weathering

RECOMMENDED USE :

suitable for the decoration and protection of all interior building surface . Typical Use ;It is ideal for application to both interior and ceiling, concretes,new and old masonry surfaces,plasters,bricks,asbestos shingled and siding.

TECHNICAL INFORMATION :

Type	100% Acrylic Emulsion Paint
Color	According to Color card
Film Appearance	Matt
Solid Content (%)	40±2
Flash Point	N/A
Dry Film Thickness	40 microns
Theoretical Coverage	150 Sqm. / Pail / Coat

Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated.

Touch Dry (25-30 °C)	30 minutes.
Recoat Dry (25-30 °C)	2 hours.
Hard Dry (25-30 °C)	72 hours.

PRODUCT STANDARD :

TIS 1123-2539 (Weather Resistance Emulsion Paint)
TIS 272-2549 (Weather Resistance Emulsion Interior Paint)

APPLICATION :

Tools	Roller / Brush / Spray
Mixing / Cleaning	Clean Water
Dilution (%)	20-25 %

Technical Data Sheet

FOUR PLUS PRO EMUSION INTERIOR

APPLICATION SYSTEM :

Surface preparation

Old Surface

Powdery and chalky surface must be scrubbed and cleaned with water Fungus and mildew growth must be cleaned off . Left to dry for 2-3 days

New Surface

Substrate must be completely cured and dried (~ 1 month) free from oil ,grease ,mildew,from release agents and foreign matters.or measure moisture which should be less than 15% on surface with protimeter mini If any crack, it should be repaired on surface before applying.

Painting System

Primer for Old Surface

1 Coat of NEOCOAT MASONRY SEALER

Primer For New Surface

1 Coat of FOUR PLUS PRO MASONRY SEALER

Topcoat

2 Coats of FOUR PLUS PRO INTERIOR

HANDLING AND STORAGE :

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Shelf Life

2 years

Packing

18.925 Ltr.

HEALTH AND SAFETY :

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.