

# Technical Data Sheet

## FOUR PLUS PRO EMUSION INTERIOR

**PRODUCT DESCRIPTION :**

Premium grade emulsion paint for building applications, formulated from acrylic resin. The product is free from lead and mercury. The paint film provides high flexibility up to 300%, with excellent resistance to moisture, waterproofing capability, anti-corrosion, and abrasion resistance. It is easy to clean, available in a wide range of shades, and delivers long-lasting beauty and durability to surfaces.

**RECOMMENDED USE :**

Suitable for concrete roof decks for waterproofing and weather protection. It can also be applied on building walls to effectively cover cracks and hairlines. Recommended for concrete sports surfaces such as basketball and volleyball courts, with customizable color shades available upon request.

**TECHNICAL INFORMATION :**

Type	100% Acrylic Emulsion Paint
Color	According to Color card
Film Appearance	Matt / Semi Gloss
Solid Content (%)	
Flash Point	N/A
Dry Film Thickness	40      microns
Theoretical Coverage	150      Sqm. / Pail / Coat
<p>Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated.</p>	
Touch Dry (25-30 °C)	30      minutes.
Recoat Dry (25-30 °C)	2      hours.
Hard Dry (25-30 °C)	72      hours.

**APPLICATION :**

Tools	Roller / Brush / Spray
Mixing / Cleaning	Clean Water
Dilution (%)	20-25    %

## Technical Data Sheet

# FOUR PLUS PRO EMUSION INTERIOR

### APPLICATION SYSTEM :

#### Surface preparation

##### New Surface

Substrate must be completely cured and dried ( ~ 1 month ) free from oil ,grease ,mildew,from release agents and foreign matters.or measure moisture which should be less than 15% on surface with protimeter mini If any crack, it should be repaired on surface before applying.

##### Old Surface

The surface must be clean, free from dust, grease, oil stains, wax, salt deposits, old paint, and any contaminants.

Chalky or deteriorated surfaces must be scrubbed clean using a nylon brush.

Clean the surface with water and appropriate cleaning agents, then rinse with clean water and allow the surface to dry completely.

#### Painting System

##### Concrete Floor

Moisture Barrier Primer  
Primer  
Top

Superflor BH Clear 1-2 coats  
Unique Flex Ibility Primer / Unique Flex 8000 Primer White 1 coat  
Unique Flex Color 2 coats

##### Building Wall

Primer (New Surface)  
Primer (Old Surface)  
Top

Unique Flex 8000 Primer White 1 coat  
Neocoat Masonry Sealer 1 coat  
Unique Flex Color 2 coats

##### Sports Court

Moisture Barrier Primer  
Surface Leveling  
Primer  
Top

Superflor BH Clear 1-2 coats  
Superguard EM (Non-Slip)  
Unique Flex 8000 Primer White 1 coat  
Unique Flex Flat Color 2 coats

## Technical Data Sheet

### FOUR PLUS PRO EMUSION INTERIOR

#### HANDLING AND STORAGE :

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Shelf Life

2 years

Packing

18.925 Ltr.

#### HEALTH AND SAFETY :

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.